



# ***VersaUV***

## ***LEF2-300***

Home / LEF2-300

## LEF2-300

In stock

SKU: LEF2-300



30" benchtop uv printer

DESCRIPTION SPECIFICATIONS DOWNLOADS

Qty

0

Model		LEF2-300	LEF2-200
<b>Printing method</b>		Piezo ink-jet method	
<b>Media</b>	<b>Width</b>	Max. 800 mm (31.5 in.)	Max. 538 mm (21.2 in.)
	<b>Length</b>	Max. 360 mm (14.2 in.)	Max. 360 mm (14.2 in.)
	<b>Thickness</b>	Max. 100 mm (3.94 in.)	Max. 100 mm (3.94 in.)
	<b>Weight</b>	Max. 8 kg (18 lb.)	Max. 5 kg (11 lb.)
<b>Printing width / length</b>		Max. 770 (w) × 330 (l) mm (30.3 × 13 in.)	Max. 508 (w) × 330 (l) mm (20 × 13 in.)
<b>Ink</b>	<b>Type</b>	ECO-UV (EUUV4) 220 cc cartridge, ECO-UV (EUUV4) 500 cc cartridge (White ink is not available in 500 cc cartridges.)	ECO-UV (EUUV, EUUV4) 220 cc cartridge
	<b>Colours</b>	Six colours (Cyan, Magenta, Yellow, Black, White and Gloss × 2) Six colours (Cyan, Magenta, Yellow, Black, White and Gloss) and Primer	Five colours (Cyan, Magenta, Yellow, Black and White × 2) Five colours (Cyan, Magenta, Yellow, Black and White) and Primer Six colours (Cyan, Magenta, Yellow, Black, White and Gloss) and Primer

This Roland DG Shop requires cookies to provide all of its features. By using our website, you agree to our use of cookies. [Learn more.](#)

<b>Ink-curing unit</b>		Built-in UV-LED lamp x 2	Built-in UV-LED lamp
<b>Printing resolution</b>		Max. 1440 dpi	
<b>Distance accuracy *</b>		±0.3 mm (±11.8 mil) or ±0.3% of the specified distance, whichever is greater	±0.3% of distance travelled or ±0.3 mm (±11.8 mil), whichever is greater
<b>Position reproducibility *</b>		±0.2 mm (±7.9 mil) or ±0.1% of the specified distance, whichever is greater	
<b>Connectivity</b>		Ethernet (10BASE-T/100BASE-TX, automatic switching)	
<b>Power-saving function</b>		Automatic sleep feature	
<b>Power requirements</b>		AC100 to 240 V ± 10%, 2.1 A, 50/60 Hz	AC100 to 240 V ± 10%, 1.8 A, 50/60 Hz
<b>Power consumption</b>	During operation	Approx. 178 W	Approx. 149 W
	Sleep mode	Approx. 18 W	Approx. 13 W
<b>Acoustic noise level</b>	During operation	60 dB (A) or less	
	During standby	49 dB (A) or less	
<b>Other dimensions</b>		1560 (W) × 955 (D) × 576 (H) mm (61.4 × 37.6 × 22.7 in.) When the ink cartridge tray is attached: 1866 × 955 × 576 mm (73.5 × 37.6 × 22.7 in.) ]	1202 (W) × 962 (D) × 549 (H) mm (47.3 × 37.9 × 21.6 in.)
<b>Weight</b>		144 kg (317.5 lb.)	110 kg (242.5 lb.)
<b>Environment</b>	During operation	Temperature: 20 to 32°C (68 to 90°F) (22°C (72°F) or higher recommended), Humidity: 35 to 80% RH (no condensation)	
	Not operating	Temperature: 5 to 40°C (41 to 104°F), Humidity: 20 to 80% RH (no condensation)	
<b>Included items</b>		VersaWorks 6 RIP software, power cable, cleaning liquid, drain bottle, manuals, etc.	

This Roland DG Shop requires cookies to provide all of its features. By using our website, you agree to our use of cookies. [Learn more.](#)

Hide this message



<https://www.youtube.com/watch?v=KDyCwtu8RDg&-feature=youtu.be>

## Bank Details

Beneficiary Bank: BANK OF GEORGIA JSC  
SWIFT: BAGAGE22  
Beneficiary - Name: AD TEC LLC  
Tax ID: 405 289 502  
EUR/USD/GEL Account: GE56BG0000000101477225

Agmashenebeli Alley  
12th kilometer,  
K. Gogiasvili str. #1  
0131 Tbilisi, Georgia  
office: (+995 32) 222 77 99 (ext.102)  
mob: (+995) 599 63 70 70  
email: info@adtec.ge